



**Mortite**<sup>®</sup> Inc

FLORAL CLAY

6/30/96

## MATERIAL SAFETY DATA SHEET

### SECTION I - GENERAL INFORMATION

MANUFACTURER'S NAME: MORTITE, INC.  
MANUFACTURER'S ADDRESS: 150 East 7th Street  
Paterson, NJ 07524

TELEPHONE: 201-684-5000  
FAX: 201-278-2105  
EMERGENCY TELEPHONE:

PART NUMBER & TRADE NAME: MORTITE CAULKING  
5025, 5033, 5089, 5091, 74005; Floral Clay CAGE CODE: 82814

PRODUCT DESCRIPTION: MIXTURE OF RUBBER, POLYBUTENE, AND  
INERT FILLERS  
IBM NUMBERS: 1059, 1004, 1060,  
1003, 1061

### SECTION II - HAZARDOUS INGREDIENTS

DESCRIPTION: CHEMICAL NAME: TLV: C.A.S. NO.: % BY WT.:  
THIS PRODUCT DOES NOT CONTAIN ANY HAZARDOUS INGREDIENTS.

### SECTION III - PHYSICAL PROPERTIES

BOILING POINT (F.): NOT/APP. SPECIFIC GRAVITY: 1.5 @ 77°  
VAPOR PRESSURE (mm Hg): NOT/AV. PERCENT VOLATILE (BY VOLUME): Nil  
VAPOR DENSITY (AIR=1): NOT/APP. EVAPORATION RATE: NOT/APP.  
SOLUBILITY IN WATER: NEGLIGIBLE  
APPEARANCE AND ODOR: GREEN OR WHITE TACKY MASTIC, MILD ODOR

### SECTION IV - FIRE AND EXPLOSION DATA

FLASH POINT: 400°F FLAMMABLE LIMITS: Lel\_\_Uel\_\_ N/AV  
(METHOD USED): COC

EXTINGUISHING MEDIA--FOAM:\_\_\_\_ ALC. FOAM:\_\_\_\_ CO2:\_\_\_\_  
DRY CHEMICALS:\_\_\_\_ WATER: X OTHER:\_\_\_\_

SPECIAL FIRE FIGHTING PROCEDURES: WEAR SELF-CONTAINED BREATHING APPARATUS  
WHEN FIGHTING FIRES.

UNUSUAL FIRE AND EXPLOSION HAZARDS: DENSE BLACK SMOKE, CO., CO, ACRID ODOR,  
MAY CAUSE TEARING OF EYES

#### DISCLAIMER

The information contained herein is believed to be accurate and is offered in good faith. Because product use is beyond our control, no warranty is given, expressed or implied. The company cannot assume any liability for the use of information contained herein.

**SECTION V - HEALTH HAZARD DATA**

ACUTE AND CHRONIC EFFECTS OF OVEREXPOSURE: NO KNOWN HAZARD  
EFFECTS OF OVEREXPOSURE: NO KNOWN HAZARD  
EMERGENCY AND FIRST AID PROCEDURES: FIRST AID IS NOT NORMALLY REQUIRED;  
NO HAZARD UNDER NORMAL USE. SKIN: REMOVE WITH SOAP AND WATER; EYES:  
FLUSH WITH WATER

**SECTION VI - REACTIVITY DATA**

STABILITY:	UNSTABLE-___ STABLE- <u>X</u>
INCOMPATIBILITY (MATERIALS TO AVOID):	NONE ESTABLISHED
HAZARDOUS DECOMPOSITION PRODUCTS:	CARBON MONOXIDE AND UNIDENTIFIED COMPOUNDS MAY BE FORMED DURING COMBUSTION.
HAZARDOUS POLYMERIZATION:	MAY OCCUR-___ WILL NOT OCCUR- <u>X</u>
CONDITIONS TO AVOID:	NONE

**SECTION VII - SPILL OR LEAK PROCEDURES**

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: NOT/APP.  
WASTE HANDLING AND DISPOSAL METHOD: IN ACCORDANCE WITH LOCAL SOLIDS  
DISPOSAL PRACTICES.  
EPA HAZARDOUS SUBSTANCE CATEGORY: N/A  
(40 CFR 116-117)

**SECTION VIII - OCCUPATIONAL PROTECTIVE MEASURES**

RESPIRATORY PROTECTION:	NONE NEEDED
VENTILATION:	MECHANICAL (GENERAL)
PROTECTIVE GLOVES:	NO
EYE PROTECTION:	NO
OTHER PROTECTIVE EQUIPMENT:	NONE NEEDED

**SECTION IX - SPECIAL PRECAUTIONS**

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: NONE - NORMAL BULK  
STORAGE AND HANDLING IN ACCORDANCE WITH NFPA RECOMMENDATIONS.

**SECTION X - TRANSPORTATION**

APPLICABLE REGULATIONS:	49 CFR
PROPER SHIPPING NAME:	CAULKING COMPOUND NOIBN
UN NO.:	NOT APPLICABLE
HAZARD CLASS:	NOT APPLICABLE LABELS REQ.: NONE
EPA HAZARDOUS WASTE NO.:	NOT APPLICABLE

ABOVE INFORMATION BASED ON LABORATORY TESTS? NO; FROM MSDS OF RAW MATERIAL  
SUPPLIERS.